AMENDMENTS TO THE CLAIMS

-2-

Please amend claims 1, 3, 4, 5, 8, 9, 11, 12, 14, 15, 19, 21, 23, 24, 25, 26, 27, 29, 30, cancel claims 16-18, and add new claims 32-39 such that the status of the claims is as follows: 1. (Currently amended) A distributed control and/or monitoring system within an industrial plant, the system comprising:

a control/monitoring center;

a plurality of field devices within the industrial plant having no hardwired communication link to the control/monitoring center and each other, each field device comprising: a transducer;

a wireless transceiver for communicating wirelessly; and a plant-wide power bus for delivering power to each field device.

- The distributed system of claim 1 wherein each field device further comprises: 2. (Original) a power circuit for controlling power delivery from the power bus to the transducer and to the wireless transceiver within the field device.
- 3. (Currently amended) The distributed system of claim 1 wherein each the plant-wide power bus is a single wire bearing a voltage.
- 4. (Currently amended) The distributed system of claim 1 wherein each of the plurality of field devices communicates wirelessly with the control/monitoring center.
- 5. (Currently amended) The distributed system of claim 1 wherein some of the plurality of field devices are positioned within close proximity to one another in a cluster, the system further comprising:

a power circuit <u>connected to the plant-wide power bus</u> for controlling power supplied to the cluster of field devices.

- 6. (Original) The distributed system of claim 5 wherein the power circuit further comprises:

 a ground loop connected to earth ground for electrically grounding each of the field devices in the cluster of field devices.
- 7. (Original) The distributed system of claim 5 wherein each field device is individually grounded to earth.
- 8. (Currently amended) A distributed system for monitoring an industrial process within an industrial plant, the system comprising:

a control/monitoring center;

- a plurality of field devices for sensing or altering the industrial process, each field device having a transducer and a wireless transceiver for communicating signals between the field device and the control/monitoring center; and
- a <u>plant-wide power bus comprising a</u> wire carrying an unfiltered voltage potential for delivering a voltage potential to each of the plurality of field devices.
- 9. (Currently amended) The distributed system of claim 8 wherein each of the plurality of field devices further comprises:
 - a voltage regulator for controlling power delivered <u>from the plant-wide power bus</u> to the wireless transceiver.

First Named Inventor: Robert J. Karschnia

10. (Original) The distributed system of claim 9 wherein each of the plurality of field devices further comprises:

-4-

a direct connection to a ground.

11. (Currently amended) The distributed system of claim 8 wherein two or more of the plurality of field devices, which are in close proximity to one another, constitute a group, and further comprising:

a power supply for stepping down an existing alternating or direct current voltage <u>from the</u>

<u>plant-wide power bus</u> to a lower voltage, wherein a single wire is connected from each field device to the power supply.

12. (Currently amended) The distributed system of claim 8 wherein at least one each field device further comprises:

a power regulation circuit for stepping down an existing alternating or direct current voltage <u>from the plant-wide power bus</u> to the voltage potential for delivery to the field device via the wire.

- 13. (Original) The distributed system of claim 8 wherein the voltage potential is less than five volts.
- 14. (Currently amended) A distributed control and/or monitoring system in an industrial plant, the system comprising:

a control/monitoring center;

a plurality of field devices, each field device having a transducer;

a plurality of wireless transceivers, each wireless transceiver for sending and receiving wireless signals between the control/monitoring center and one or more of the

First Named Inventor: Robert J. Karschnia Application No.: 10/734,889

-5-

plurality of field devices, each wireless transceiver being in electrical communication with at least one of the plurality of field devices; and power supplies for supplying power from a plant-wide power bus an existing power circuit to the wireless transceivers and to the plurality of field devices.

15. (Currently amended) The distributed system of claim 14 wherein the <u>plant-wide power bus existing</u> power circuit is a standard AC or DC circuit.

16-18. (Canceled)

19. (Currently amended) A method for retrofitting an existing field device network in an industrial plant for wireless communications, the method comprising:

installing a first wireless transceiver in communication with a control/monitoring center; installing a second wireless transceiver on an existing <u>plant-wide</u> power bus and in communication with one or more field devices; and

configuring the second wireless transmitter to communicate with the one or more field devices and to transmit data wirelessly from the one or more field devices to the control/monitoring center in addition to data transmitted over an existing communication link.

20. (Original) The method of claim 19 further comprising:

installing a "smart" field device on the fieldbus network, the "smart" field device having a wireless transceiver, the "smart" field device for providing diagnostic information to the control center.

Application No.: 10/734,889

21. (Currently amended) A distributed field device system comprising:

a single-wire plant-wide power bus; and

a plurality of wireless field devices, each wireless field device comprising:

a transducer;

First Named Inventor: Robert J. Karschnia

a wireless transceiver for sending information from the transducer to a control center; and

power circuitry for drawing adequate power from the single-wire <u>plant-wide</u>
power bus to power the transducer and the wireless transceiver.

- 22. (Original) The distributed field device system of claim 21 wherein each of the plurality of wireless field devices is electrically grounded.
- 23. (Currently amended) A field device for use in an industrial plant having a plant-wide power bus, the field device comprising:

a transducer;

a wireless transceiver;

a power terminal for connecting the field device to the plant-wide [[a]] power bus;

a ground connection for electrically grounding the field device; and

an internal power supply circuit connected to the power terminal and the ground connection for supplying power to the transducer and the wireless transceiver.

24. (Currently amended) The field device of claim 23 wherein the <u>plant-wide</u> power bus is a single wire carrying a voltage potential other than zero, and the power terminal is connectable to the single wire.

25. (Currently amended) The field device of claim 23 wherein the field device is connectable connected

-7-

- directly to ground via the ground connection.
- 26. (Currently amended) A field device for use in an industrial plant having a plant-wide power bus, the <u>field device</u> comprising:
 - a housing;
 - a circuit disposed within the housing, the circuit comprising:
 - a wireless transceiver for wireless communication with a control/monitoring center;
 - a transducer; and
 - an electrical terminal connectable to the plant-wide power bus for delivering power to the wireless transceiver and the transducer from an existing power circuit the plant-wide power bus.
- 27. (Currently amended) The field device of claim 26 wherein the plant-wide power bus existing power circuit is an AC or DC circuit.
- 28. (Original) The field device of claim 26, further comprising: a ground connection for grounding the circuit.
- 29. (Currently amended) A field device for use in an industrial plant having a plant-wide power bus, the field device comprising:
 - a transducer and/or an actuator;
 - a wireless transceiver; and
 - a power supply circuit connectable to the plant-wide power bus for delivering power to the transducer and/or the actuator and to the wireless transceiver.

Application No.: 10/734,889

30. (Currently amended) The field device of claim 29 wherein the power supply circuit is connected connectable to a standard electrical outlet of the plant-wide power bus.

- 31. (Original) The field device of claim 29 wherein the field device is connected wirelessly with a network.
- 32. (New) A distributed control and/or monitoring system comprising:
 - a control/monitoring center;
 - a plurality of field devices, each field device having a transducer;
 - a plurality of wireless transceivers, each wireless transceiver for sending and receiving wireless signals between the control/monitoring center and one or more of the plurality of field devices, each wireless transceiver being in electrical communication with at least one of the plurality of field devices;
 - power supplies for supplying power from an existing power circuit to the wireless transceivers and to the plurality of field devices;
 - a four-wire bus comprising:
 - a two-wire power bus in electrical communication with each of the power supplies; and
 - a two-wire communication bus connecting the control center with each field device;
 - wherein the wireless transducer wirelessly transmits data from each sensor to the control center that is not otherwise transmitted over the two-wire communication bus.
- 33. (New) A distributed control and/or monitoring system comprising: a control/monitoring center;

Application No.: 10/734,889

a plurality of field devices, each field device having a transducer;

a plurality of wireless transceivers, each wireless transceiver for sending and receiving wireless signals between the control/monitoring center and one or more of the plurality of field devices, each wireless transceiver being in electrical communication with at least one of the plurality of field devices;

power supplies for supplying power from an existing power circuit to the wireless transceivers and to the plurality of field devices;

a two-wire bus connecting the field devices and the control/monitoring center; and wherein the wireless transceivers transmit data wirelessly from the field devices that is not otherwise transmitted over the two-wire bus.

- 34. (New) A distributed control and/or monitoring system comprising:
 - a control/monitoring center;
 - a plurality of field devices having no hardwired communication link to the control/monitoring center and each other wherein each of the plurality of field devices communicate wirelessly with the control/monitoring center through a self-organizing wireless network, each field device comprising:
 - a transducer;
 - a wireless transceiver for communicating wirelessly; and a common power bus for delivering power to each field device.
- 35. (New) The distributed system of claim 34 wherein each field device further comprises:

 a power circuit for controlling power delivery from the power bus to the transducer and
 to the wireless transceiver within the field device.

First Named Inventor: Robert J. Karschnia Application No.: 10/734,889

-10-

36. (New) The distributed system of claim 34 wherein each the power bus is a single wire bearing a voltage.

- 37. (New) The distributed system of claim 34 wherein some of the plurality of field devices are positioned within close proximity to one another in a cluster, the system further comprising:

 a power circuit for controlling power supplied to the cluster of field devices.
- 38. (New) The distributed system of claim 37 wherein the power circuit further comprises:

 a ground loop connected to earth ground for electrically grounding each of the field devices in the cluster of field devices.
- 39. (New) The distributed system of claim 37 wherein each field device is individually grounded to earth.